



FEATURES

■ *The ZX41 Pressure Transmitter is a tried and tested member of our range of advanced control peripherals. Aimed primarily at Dust Extraction and Air Flow applications, this transmitter unit has an electronic control system and responds accurately to pressure differences sensed at the pneumatic receptors with a linear 4-20mA output. The unit is factory calibrated to suit the following pressure ranges:-*

- Pt. No. ZX41(4i).....0 - 4i Water gauge*
- Pt. No. ZX41(10i).....0 - 10i Water gauge*
- Pt. No. ZX41(25i).....0 - 25i Water gauge*
- Pt. No. ZX41(100mm).....0 - 100mm Water gauge*
- Pt. No. ZX41(250mm).....0 - 250mm Water gauge*
- Pt. No. ZX41(625mm).....0 - 625mm Water gauge*

Pneumatic bulkhead fitting types are specified by adding iCi to the part number for compression type (as shown above) and iPi for push-fit (rapid) type connectors.

The ZX41 is fully compatible with all our KX and ZX ranges of monitors. Its singularly robust and simple design guarantees no resetting or recalibration would be needed as a result of disconnection or power failure, ensuring seamless operation at all times. Attractively packaged and weather-proof to IP65 specifications, this unit can confidently be used with a variety of systems - wherever versatile and accurate pressure monitoring is required.

Circuit Control Technology Ltd.
Omni House, Sheene Road
Gorse Hill Industrial Estate
Beaumont Leys, Leicester, LE4 1BF
Tel: +44 (0) 116 2998000
Fax: +44 (0) 116 2998001
e-mail: info@circuitcontroltechnology.com

Contents

Features	1
Technical Specifications	2

Technical Specifications

UNIT:	Part Number ZX41
INPUT SUPPLY:	Loop powered 15 - 40Vdc.
INPUT FUSES:	This equipment is not fused.
POWER SUPPLY:	Loop powered - see above
MAINS FAILURE:	In the event of power failure, the unit will operate to specification when the voltage level comes within the above limits.
START UP SEQUENCE:	The unit is arranged so that pressure reading and 4-20mA output will start immediately.
PRESSURE SCALE:	0 - 100, 0 - 250, 0 - 625mmWG 0 - 4", 0 - 10", 0 - 25" WG.
DP PRESSURE CONNECTIONS	2 x 5mm (outside dia.) pneumatic compression or push-fit (rapid) connectors suitable to accept nylon hose.
CONSTRUCTION:	Solid state components mounted on a single-sided glass fibre P.C.B with component legend.
INDICATION:	This equipment has no on-board visual display.
AMBIENT TEMPERATURE AT BOARD SURFACE:	-10 to +45 deg.C.
STORAGE TEMPERATURE:	-20 to + 70 deg.C.